



pravaklíma
v objemu doma



Toplotna črpalka

Altherma 3 M



Toplotna črpalka

Altherma 3 M



Monoblok toplotna črpalka zrak-voda z naprednim dizajnom in visoko učinkovitostjo, ki uporablja plin R32, je primerna za manjše prostore ter tudi večje zgradbe.



Sodoben izgled



Ogrevanje prostorov



Hladilno sredstvo



Brezžično upravljanje

Idealna izbira za manjši dom

Ker gre za toplotno črpalko z le eno zunanjo enoto (monoblok), je to odlična rešitev za manjše prostore, kjer ne bo zavzela nič notranjega prostora. Naprava namreč deluje brez notranje enote.

Najbolj prijetna toplina doma

Daikin Altherma 3 M je toplotna črpalka, ki zagotavlja izboljšano učinkovitost vse do A+++ in delovanje do zunanje temperature - 25 °C. Tako vam bo v vašem domu vedno prijetno toplo.



Enota se zlije z zunanjim okoljem

Altherma 3 M



Technical specifications				EDLA09DV3		EDLA11DV3		EDLA14DV3		EDLA16DV3							
Heating capacity		Nom.		kW		9.37 (1) / 9.00 (2)		10.6 (1) / 9.82 (2)		12.0 (1) / 12.5 (2)		16.0 (1) / 16.0 (2)					
Power input		Heating		Nom.		kW		1.91 (1) / 2.43 (2)		2.18 (1) / 2.68 (2)		2.46 (1) / 3.42 (2)		3.53 (1) / 4.56 (2)			
COP						4.91 (1) / 3.71 (2)		4.83 (1) / 3.66 (2)		4.87 (1) / 3.64 (2)		4.53 (1) / 3.51 (2)					
Casing		Colour		Silver													
		Material		Polyester painted galvanised steel plate													
Dimensions		Unit		Height		mm		870									
				Width		mm		1,380									
				Depth		mm		460									
		Packed unit		Height		mm		1,053									
				Width		mm		1,520									
				Depth		mm		650									
Weight		Unit		kg		147											
		Packed unit		kg		164											
Packing		Material		PE wrapping foil / Carton / Wood (pallet)													
		Weight		kg		17											
Heat exchanger		Length		mm		1,136 / 1,166 / 1,195											
		Rows		Quantity		3											
		Fin pitch		mm		1.4											
		Passes		Quantity		14											
		Face area		m²		0.950 / 0.970 / 1.00											
		Stages		Quantity		38											
		Tube type				7.0 Hi-XD											
		Fin		Type		WF fin											
				Treatment		Anti-corrosion treatment											
Fan		Type		Propeller fan													
		Quantity		1													
		Discharge direction		Horizontal													
		Air flow rate		Heating		High		m³/min		48.0		55.8		70.4		85.0	
Fan motor		Quantity		1													
		Model		Brushless DC motor													
		Speed		Steps		8											
				Heating		Nom.		rpm		400		450		550		650	
		Output						W		230							
		Drive				Direct drive											

Povzeto po katalogih Daikin.

Pridržujemo si pravico do spremembe podatkov v primeru tiskarske napake.

**Z vami od
leta 2015.**

 **pravaklima**

www.pravaklima.si

info@pravaklima.si

069 773 173

